

MIL087081

MILS67-1200 LED 5000 HF TW PC 840 M20

Elnumber:

EAN-nr: 7054130870814

Stock code: M



This is a sample image. This item may be of a different colour or otherwise differ from the image displayed.



Electrical data	
Maximum voltage +10% (V)	240
Maximum frequency +5% (Hz)	60
Minimum frequency -5% (Hz)	50
Minimum Voltage -10% (V)	220
Number of fixtures on a MCB16 type C fuse	21
Total consumption (W)	37
Number of fixtures on a MCB16 type B fuse	12
Number of fixtures on a MCB10 type B fuse	8
Number of fixtures on a MCB10 type C fuse	13
Termination	
Type of blind-plug	M20-Polyamide
Number of cable glands	2
Number of blind plugs	2
Termination	5x6mm ² screw terminal block
Type of cable gland	M20-Polyamide
Type of through wiring	5x2,5
Maximum cable diameter	14
Minimum cable diameter	7
Technical data	
Maximum ambient temperature (°C)	55
IK Classification	10
Minimum ambient temperature (°C)	-40
IP classification	66/67
Ballast/Driver	
Type of ballast/driver	HF (High frequency)
Number of ballast/driver	1

Light data	
Light source	LED
Lamp code supplied light source	CRI >80, 4000K
Luminous flux decline (LLMF) LED 50000h Ta25	0.90
MacAdam step	3
System Lumen/Watt	139
Rated system lifetime at Ta max°C	50000h L80B50
Rated system lifetime at Ta 25°C	100.000h
System Lumen Out	5130
Dimensions	
Net weight (kg)	6
Width (mm)	165
Height (mm)	128
Length (mm)	1334
CCmax (mm)	1314
CCmin (mm)	1314
Body	
Colour of body	White
Body material	Stainless Steel AISI 316L
Body colour code	RAL9016
Optic	
Material of diffuser	Polycarbonate
Lightdistribution Up/Down	5/95

MIL087081

Drawings

MIL LED	L1 (mm)	C1 (mm)	L (mm)	C for Hood nut
MIL-600 LED	724	704	681	On request
MIL-1200 LED	1334	1314	1291	On request
MIL-1500 LED	1634	1614	1594	On request

