



SL1IR Searchlight Complete/FLIR640-20m/Standing/Wh/DC-3m/OP

Based on the SL1 searchlight here with a fully integrated FLIR Boson Thermal camera for Night vision capability. Together with the white LED light an unbeatable tool for visability. Here as a complete set for standing mount.

Item Number	LNSLS-11626-W
GTIN	7072720011324
Stock status	М



Certificates
















Cerunicales	
Marine Approved	True
Technical Data	
Minimum ambient temperature (°C)	-40
Maximum ambient temperature (°C)	55
IP classification	66/67
Corrosion class	C5-M
Operation mode	IR camera, Remote Luminell
Light Technical Data	
Light source	LED
Lumen out (Im)	20000
Number of lamps	2
Lumen value supplied light source (lm)	20000
Power consumption light source (W)	200
Lumen per Watt (Im/W)	100
CRI Colour rendering index	70
Candela Output (cd)	1800000
Light source 2	LED
Number of lamps 2	1
Lumen value supplied light source 2 (lm)	12000
Power consumption light source 2 (W)	120

Electrical Data		
EMC Category	EMC1: EMC	C B – IEC 60533 Bridge and
, , ,		Open deck
Main Feed DC (V)		18
Min		
Main Feed DC (V)		30
Max		
Total consumption		500
(W)		
Optic		
Output angle (°)		Spot 3,5 / Flood 15
Focus		Yes
Llouging		
Housing		Seawater-resistant
Main body material		Seawater-resistant aluminium
Main body material p	roduction	Die-casted
method		2.0 040104
Main Body MaterialTe	ext	Anodized and powder
		coated
Surface treatment		Powder Coated
Body colour		White
Main body colour nar	ne	Traffic white
Main body colour sur	face	Powder coated
Main body colour RA	L code	RAL 9016
Dimensions		
Net weight (kg)		24.00004
not worgint (kg)		20000-



Special	
PAN Sector	Endless rotation
TILT Sector	120
Logistic Data	
Item gross weight (kg)	26.087

Illustrations



SL1 Measurement Drawing