

500106940

SL40 R5 Halogen



SL40 R5 SH310 230V 1000W C

Elnumber:

EAN-nr: 7070404033273

Stock code: A

The SL40 R5 is designed with a IP56 rating and is approved for temperatures down to -40°C and up to +50°C. Seawater resistant aluminum housing and motor house, coupled with excellent heat management, ensures a searchlight with long run-time and long lifetime. THIS ITEM IS DELIVERED WITH PANEL, BUT NO FOCUS.



Technical data

IP classification	56
Maximum ambient temperature (°C)	50
Minimum ambient temperature (°C)	-40
Operation mode	R5

Dimensions

Width (mm)	475
Diameter (mm)	380
Length (mm)	330
Gross weight (kg)	61
Height (mm)	905
Net weight (kg)	37,3

Body

Colour of body	White
Body colour code	RAL 9016
Body material	Aluminium seawater resistant

Optic

Optic	Clear
Colour of reflector	Silver
Material of reflector	Aluminium
Material of diffuser	Glass tempered

Electrical data

Maximum frequency +5% (Hz)	60
Maximum voltage +10% (V)	230
Minimum frequency -5% (Hz)	50

Light data

Number of lamps	1
Lamp power (W)	1000
Lamp base	GX9.5
Light source	QT
Candela Output (cd)	2300000
Range (m)	1540

Remarks

Remarks	C = Searchlight complete, with manual Focus (hand wheel)
---------	--

500106940

SL40 R5 Halogen

Drawings

Product	L*(m)	Angel Ω°
SL40 RS SH 310 230V 1000W C	1540	11
SL40 RS SH 470 230V 2000W C	2366	10,8
SL40 RS SH 470 230V 2000W CF	2366	10,8

* Theoretical estimated at 1 lux.

