

MIL086336

MILS67-600 LED 2500 HF TW PC 840 M20

Elnumber:

EAN-nr: 7054130863366

Stock code: C



Electrical data

Maximum voltage +10% (V)	240
Maximum frequency +5% (Hz)	60
Minimum frequency -5% (Hz)	50
Minimum Voltage -10% (V)	220
Number of fixtures on a MCB16 type C fuse	21
Total consumption (W)	19
Number of fixtures on a MCB16 type B fuse	12
Number of fixtures on a MCB10 type B fuse	8
Number of fixtures on a MCB10 type C fuse	13

Termination

Type of blind-plug	M20-Polyamide
Number of cable glands	2
Number of blind plugs	2
Termination	5x6mm ² screw terminal block
Type of cable gland	M20-Polyamide
Type of through wiring	5x2,5
Maximum cable diameter	14
Minimum cable diameter	7

Technical data

Maximum ambient temperature (°C)	55
IK Classification	10
Minimum ambient temperature (°C)	-40
IP classification	66/67

Ballast/Driver

Type of ballast/driver	HF (High frequency)
Number of ballast/driver	1

Light data

Light source	LED
Lamp code supplied light source	CRI >80, 4000K
Luminous flux decline (LLMF) LED 50000h Ta25	0.90
MacAdam step	3
System Lumen/Watt	135
Rated system lifetime at Ta max°C	50000h L80B50
Rated system lifetime at Ta 25°C	100.000h
System Lumen Out	2565

Dimensions

Net weight (kg)	3,9
Width (mm)	165
Length (mm)	724
Height (mm)	128
CCmax (mm)	704
CCmin (mm)	704

Body

Colour of body	White
Body material	Stainless Steel AISI 316L
Body colour code	RAL9016

Optic

Material of diffuser	Polycarbonate
Lightdistribution Up/Down	5/95

MIL086336

Drawings

