

FL70 LED FLOODLIGHT

Application	Decks and holds, ramps, industrial areas
Protection degree	IP66/67
Housing	Seawater resistant aluminum anodized
Mounting	Adjustable stainless steel bracket with mounting holes, Ø 11/14mm
Diffuser	Borosilicate clear glass
Cable entry	JB (Junction Box) 2xM25x1.5 brass nickel plated D9-17mm or FL (5m cable) version
Light source	LED, CRI >80, 5000K
Light output	27.000 / 54.000 lm
Lifetime	100.000 hours at Ta 45°
Power consumption	183W (per module)
Operating voltage	220-254V AC - 50/60 Hz
Temperature range	-35°C / +55°C
Beam angles	SB 18° - XNB 27° - XNB 39° - NB 60° - MB 80° - WB 100° - XWB 120°



JB version



FL version

JB version

With junction box on the back of the light.

FL version

Flying Lead version, with 5 m cable. The FL version can be connected to an JB version

HOLLAND STANDARD

FL70

FL version

JB version

FL version



FL70 27000 JB

FL70000000	FL70 27000 850 220-254 BN25 SB-18 JB	10 kg
FL70001000	FL70 27000 850 220-254 BN25 XNB-27 JB	10 kg
FL70002000	FL70 27000 850 220-254 BN25 XNB-39 JB	10 kg
FL70003000	FL70 27000 850 220-254 BN25 NB-60 JB	10 kg
FL70004000	FL70 27000 850 220-254 BN25 MB-80 JB	10 kg
FL70005000	FL70 27000 850 220-254 BN25 WB-100 JB	10 kg
FL70006000	FL70 27000 850 220-254 BN25 XWB-120 JB	10 kg



LxWxD
403mm x 288mm x 245mm



LxWxD
403mm x 288mm x 145mm

FL70 27000 FL

FL70100000	FL70 27000 850 220-254 SB-18 FL	9,5 kg
FL70101000	FL70 27000 850 220-254 XNB-27 FL	9,5 kg
FL70102000	FL70 27000 850 220-254 XNB-39 FL	9,5 kg
FL70103000	FL70 27000 850 220-254 NB-60 FL	9,5 kg
FL70104000	FL70 27000 850 220-254 MB-80 FL	9,5 kg
FL70105000	FL70 27000 850 220-254 WB-100 FL	9,5 kg
FL70106000	FL70 27000 850 220-254 XWB-120 FL	9,5 kg

FL70 54000 JB

FL70200000	FL70 54000 850 220-254 BN25 SB-18 JB	19,8 kg
FL70201000	FL70 54000 850 220-254 BN25 XNB-27 JB	19,8 kg
FL70202000	FL70 54000 850 220-254 BN25 XNB-39 JB	19,8 kg
FL70203000	FL70 54000 850 220-254 BN25 NB-60 JB	19,8 kg
FL70204000	FL70 54000 850 220-254 BN25 MB-80 JB	19,8 kg
FL70205000	FL70 54000 850 220-254 BN25 WB-100 JB	19,8 kg
FL70206000	FL70 54000 850 220-254 BN25 XWB-120 JB	19,8 kg



LxWxD
409mm x 588mm x 245mm