

HOLLAND STANDARD

FL60

FL60 LED FLOODLIGHT

Application	Decks and holds, ramps, industrial areas
Protection degree	IP66/67
Housing	Seawater resistant aluminum anodized Frame and bracket stainless steel
Pane	Polycarbonate
Temperature range	-45°C up to +55°C
Lifetime	100.000 hours at Ta 45°
Cable entry	M24x1,5 nickel plated brass
Light source	LED - 40W per module
Operating voltage	120V or 230V 50/60Hz
Mounting	Adjustable bracket with mounting holes, Ø 11/14mm



PART NO.

- [FL6010X000](#) 1 x 40W 230V 50/60Hz
- [FL6020X000](#) 2 x 40W 230V 50/60Hz
- [FL6030X000](#) 3 x 40W 230V 50/60Hz
- [FL6040X000](#) 4 x 40W 230V 50/60Hz

[FL60S40000](#) 4x40W 230V 50/60Hz spotbeam

X = 0 Narrow Beam 60°
 X = 1 Medium Beam 90°
 X = 2 Wide Beam 120°
 Spotbeam = 10°

WEIGHT

- 6,0 kg
- 11,2 kg
- 14,1 kg
- 16,3 kg

20 kg



HOLLAND STANDARD

FL60

