

FX60 EX LED FLOODLIGHT

Application	Hazardous areas zone 1 and zone 2
Protection degree	IP66/67
Housing	Modules out of di-casting, seawater resistant aluminium, frame and bracket out of stainless steel AISI 316
Pane	Polycarbonate
Light output	4500lm per module
Cable entry	M24x1,5 nickel plated brass
Light source	LED 40W for each module
Mounting	Adjustable bracket with mounting holes, diameter 11/14mm



NB = Narrow Beam = 60°
 MB = Medium Beam = 90°
 WB = Wide Beam = 120°

PART NO.

FX60100000	1 x 40W 230V 50/60Hz M25 NB
FX60101000	1 x 40W 230V 50/60Hz M25 MB
FX60102000	1 x 40W 230V 50/60Hz M25 WB
FX60200000	2 x 40W 230V 50/60Hz M25 NB
FX60201000	2 x 40W 230V 50/60Hz M25 MB
FX60202000	2 x 40W 230V 50/60Hz M25 WB
FX60300000	3 x 40W 230V 50/60Hz M25 NB
FX60301000	3 x 40W 230V 50/60Hz M25 MB
FX60302000	3 x 40W 230V 50/60Hz M25 WB
FX60400000	4 x 40W 230V 50/60Hz M25 NB
FX60401000	4 x 40W 230V 50/60Hz M25 MB
FX60402000	4 x 40W 230V 50/60Hz M25 WB

WEIGHT

7.5 kg
7.5 kg
7.5 kg
14 kg
14 kg
14 kg
17.6 kg
17.6 kg
17.6 kg
20.5 kg
20.5 kg
20.5 kg



HOLLAND STANDARD

FX60

