

HOLLAND STANDARD

SERIES 60/61

NAVIGATION LIGHTS SERIES 60/61

| | |
|--------------------------|--|
| Application | Series 60: vessels from 20 to 50 m Series 61: vessels >50 m |
| Protection degree | IP66/IP67 |
| Housing | Polycarbonate housing and housing cover. Borosilicate glass. Top: Seawater resistant aluminium Stainless screws and nuts (Hex. nuts M6) |
| Light source | High power LED (included) |
| Mounting | Cable gland M25 x 1.5 Polyamide, for outer cable \varnothing 9,00-17,00 mm Up to 400 m cable run |



PART NO.

| | | |
|----------------------------|--------------------------------|-------------|
| 366920X000 | S60 Port, 2nm | 1,7kg / 2kg |
| 366810X000 | S60 Starboard, 2nm | 1,7kg / 2kg |
| 366600X000 | S60 Masthead, 5nm | 1,7kg / 2kg |
| 366770X000 | S60 Stern white, 2nm | 1,7kg / 2kg |
| 366740X000 | S60 Stern yellow, 2nm | 1,7kg / 2kg |
| 366570X000 | S60 Signal white, 2nm | 1,7kg / 2kg |
| 366510X000 | S60 Signal green, 2nm | 1,7kg / 2kg |
| 366520X000 | S60 Signal red, 2nm | 1,7kg / 2kg |
| 366570X003 | S60 Signal white (2x180°), 2nm | 1,7kg / 2kg |
| 366510X003 | S60 Signal green (2x180°), 2nm | 1,7kg / 2kg |
| 366520X003 | S60 Signal red (2x180°), 2nm | 1,7kg / 2kg |
| | | |
| 367420X000 | S61 Port, 3nm | 1,7kg / 2kg |
| 367310X000 | S61 Starboard, 3nm | 1,7kg / 2kg |
| 367100X000 | S61 Masthead, 6nm | 1,7kg / 2kg |
| 367270X000 | S61 Stern white, 3nm | 1,7kg / 2kg |
| 367240X000 | S61 Stern yellow, 3nm | 1,7kg / 2kg |
| 367070X000 | S61 Signal white, 3nm | 1,7kg / 2kg |
| 367010X000 | S61 Signal green, 3nm | 1,7kg / 2kg |
| 367020X000 | S61 Signal red, 3nm | 1,7kg / 2kg |
| 367070X003 | S61 Signal white (2x180°), 3nm | 1,7kg / 2kg |
| 367010X003 | S61 Signal green (2x180°), 3nm | 1,7kg / 2kg |
| 367020X003 | S61 Signal red (2x180°), 3nm | 1,7kg / 2kg |

X = 3 : 24V DC (1,7kg)
X = 5 : 115-230V AC (2kg)

WEIGHT

