

### DL41-R155 LED DOWNLIGHT


- Application:** Cabin and public areas as cabins, corridors, stair cases, lounges and shopping areas.
- Housing:** Housing of painted and galvanized steel, white coloured. Trims of painted or chromed steel or brushed aluminum.
- Diffuser:** Silver matt aluminium reflector and opalic polycarbonate diffuser, clear diffuser also available
- Cable entry:** Cable with quick connector Wago (QCA) or Ensto (QCE) or cable with connection box that has push in terminal block
- Light source (incl.):** LED
- Light temperature:** 3000K or 4000K on request
- Electric:** Integrated on/off with phase cut dimming option (HF), nightlight option (HF-NL) or UPS version (HF-Z).
- Voltage:** 220-240V or 110V; 50/60Hz
- Mounting:** Recessed mounting, fixed with 3 screws. No ceiling thickness limitation.
- Cut-out:** Ø 145mm or Ø 155mm



Designed for B0 fire protection ceiling without any need for fire hat.



155 (ALT 145)



**PART NO.**

- [DL41532962 - DL41-R155 LED 800 HF 830 1C B0 SM/WO TR](#)
- [DL41532958 - DL41-R155 LED 800 HF 830 1XQCE B0 SM/WO TR](#)
- [DL41532950 - DL41-R155 LED 800 HF 830 1XQCA B0 SM/WO TR](#)

**WEIGHT**

- 0,4kg
- 0,4kg
- 0,4kg