

DL42-R77 LED DOWNLIGHT

- Application:** Cabin and public areas as cabins, corridors, stair cases, lounges and shopping areas.
- Housing:** Housing of painted and galvanized steel, white coloured. Trims of painted or chromed steel or brushed aluminum.
- Diffuser:** Silver matt aluminium reflector and opalic polycarbonate diffuser
- Cable entry:** Cable with quick connector Wago (QCA) or Ensto (QCE) or cable with connection box that has push in terminal block
- Light source (incl.):** LED
- Light temperature:** 3000K or 4000K on request
- Electric:** Integrated on/off with phase cut dimming option (HF), nightlight option (HF-NL) or UPS version (HF-Z).
- Voltage:** 220-240V or 110V; 50/60Hz
- Mounting:** Recessed mounting, fixed with 6 self-tapping screws. To be delivered with 300 mm cable
- Cut-out:** Ø 145mm or Ø 155mm



Available versions:

- DL42 HFi Switch on/off, internal driver
- DL42 HFe Switch on/off, external driver
- DL42 24 Switch on/off, 24V DC, internal driver
- DL42 HFNL Night Light, 10-100%, internal driver
- DL42 HFDa Dimmable, 1-10V, external driver
- DL42 Dali Dimmable, DALI, external driver
- DL42 PC Dimmable, phase cut, external driver



PART NO.

- [DL42111111 - DL42 HFDa 760 38 830 QCA WH1](#)
- [DL42021203 - DL42 HFi 700 80 830 C1 CH3](#)

WEIGHT

- 0,7kg
- 0,7kg