

Main system	Series 60			Series 61		
	Range 20-50m	115V / 230V AC	24VDC	Range >50m	115V / 230V AC	24VDC
Port	2 nm	3669205000	3669203000	3 nm	3674205000	3674203000
Starboard	2 nm	3668105000	3668103000	3 nm	3673105000	3673103000
Masthead	5 nm	3666005000	3666003000	6 nm	3671005000	3671003000
Stern white	2 nm	3667705000	3667703000	3 nm	3672705000	3672703000
Stern yellow	2 nm	3667405000	3667403000	3 nm	3672405000	3672403000
Signal white	2 nm	3665705000	3665703000	3 nm	3670705000	3670703000
Signal green	2 nm	3665105000	3665103000	3 nm	3670105000	3670103000
Signal red	2 nm	3665205000	3665203000	3 nm	3670205000	3670203000
Signal white (2x180°)	2 nm	3665705003	3665703003	3 nm	3670705003	3670703003
Signal green (2x180°)	2 nm	3665105003	3665103003	3 nm	3670105003	3670103003
Signal red (2x180°)	2 nm	3665205003	3665203003	3 nm	3670205003	3670203003

Voltage supply, main system:	115V/230V AC or 24V DC
Illuminant:	LED
Ambient temperature storage and operation:	-25°C ≤ T ≤ 55°C
Protection class:	IPX6 / IPX7
Dimensions:	154 mm × 190 mm × 180 mm
Weight of plastic luminaire 24V:	1,5 kg
Weight of plastic luminaire 115V-230V:	1,9 kg
Cable gland at polycarbonate housing:	Polyamide, for outer cable diameter 9-17 mm

