

SIZES

PVC Ø (outside diameter in mm)	PVC Ø (inside diameter in mm)	Inside reach PSI plug Ø (inside diameter in mm)
32	25,6	0 + 5 to 11
40	33,6	0 + 5 to 20
50	43,6	0 + 5 to 28
75	68,6	0 + 20 to 50
110	103,6	0 + 30 to 75
125	118,6	0 + 60 to 95
160	152	0 + 86 to 125
200	190,2	0 + 124 to 154
250	237,6	150 to 184

DIN Ø (outside diameter in mm)	DIN Ø (inside diameter in mm)	Inside reach PSI plug Ø (inside diameter in mm)
42,4	37,2	0 + 5 to 19
60,3	54,5	0 + 15 to 35
88,9	82,5	0 + 30 to 62
114,3	107,1	0 + 50 to 84
139,7	131,7	0 + 70 to 102
168,3	159,3	0 + 80 to 126
219,1	207,3	0 + 122 to 164
273	260,4	0 + 150 to 202

Tolerance:

tolerance for both inner and outer size:

up to 40mm 0-1mm

40mm+ size 0-2mm

Example:

A plug 168,3-82 is suitable for sealing an outer diameter tube of 82,0-84,0mm

DH-AP Ø (outside diameter in mm)	DH-AP Ø (inside diameter in mm)	Inside reach PSI plug Ø (inside diameter in mm)
25	25,6	0 + 15 t/m 19
35	35	0 + 5 t/m 16
40	40	0 + 5 t/m 23
50	50	0 + 5 t/m 33
60	60	0 + 20 t/m 42
70	70	0 + 22 t/m 52
80	80	0 + 28 t/m 58
90	90	0 + 30 t/m 64
100	100	0 + 30 t/m 66
105	105	32-33 40-42
110	110	0 + 19-20 40-42 62-64 74-76
125	125	0 + 40 t/m 92
150	150	0 + 60 t/m 126
160	160	90-92 110-112 124-126
200	200	0 + 124 t/m 162
250	250	150 t/m 202

ASTM Ø (outside diameter in mm)	ASTM Ø (inside diameter in mm)	Inside reach PSI plug Ø (inside diameter in mm)
60,3	52,5	0 + 15 to 33
88,9	77,9	0 + 20 to 52
114,3	102,3	0 + 30 to 72
141,3	128,1	0 + 50 to 96
168,3	154,1	0 + 60 to 122
219,1	202,7	0 + 124 to 162
273	254,4	0 + 150 to 202