



# SPA-V2

PUBLIC ADDRESS & GENERAL ALARM SYSTEM

# vingtor STENTOFON

by ZENITEL GROUP

Vingtor-Stentofon products are developed by the Zenitel Group and includes a range of high quality communications equipment and systems. Being in business since 1901, Zenitel's products are recognized globally for offering high quality communications for both offshore and onshore installations. Primary system offering within the Vingtor-Stentofon portfolio are Public Address and Intercom. Zenitel and the company's global partner network, also integrate these systems with other security devices; including Radio, CCTV, Access Control and Alarm for a comprehensive security solution.

Vingtor-Stentofon is world-renowned for its extensive knowledge in the design, construction, installation and maintenance of integrated marine communication systems. Leveraging our long-term experience serving the maritime industry, we offer an impressive portfolio and provide cutting edge solutions to vessels worldwide under the brand name of Vingtor-Stentofon. The Vingtor-Stentofon brand underpins our reputation as a supplier of the most flexible, reliable and advanced communication systems available today.

## MEETING YOUR REGULATORY REQUIREMENTS

All Vingtor-Stentofon products that form a part of critical communication have been tested according to IEC 60945, IEC 60533 standards, and comply with SOLAS regulations and codes relevant to on-board communication systems. Our systems are delivered in accordance with the rules of all major classification societies.

## FOR ALL YOUR SALES & AFTER SERVICE REQUIREMENTS

Vingtor-Stentofon is a specialist provider of spare parts, repairs, maintenance contracts and refit solutions. Responsibility and availability are our guidelines and customer support and service a first priority.



2015



2013



2012



2011



2009



1952



1964



1975



1996



2001

**SPA SYSTEM DESCRIPTION** **4**

---

SPA MAIN UNITS ..... 6

SPA ACCESSORIES ..... 7

SPA INTERNAL ACCESSORIES ..... 9

SPA ANNOUNCEMENT & ALARM PANELS ..... 11

# PUBLIC ADDRESS SYSTEM

The SPA-V2 system is specially designed to meet the demands for a cost-effective Public Address system for use on board ships.

The system is available in various versions and offers a set of standard and optional features which covers the requirements for a marine Public Address and General Alarm system for all types of vessels.

Each SPA rack supports power output from 120W to 2800W. A system can consist of multiple racks to provide for the requisite capacity. The racks can be provided in the following sizes: 12 HU, 16 HU, 20 HU, and 24 HU.

The SPA system is an integrated type approved PA and GA solution. SPA is extremely cost effective where SPA loudspeaker loops are used together with the integrated ACM units to cover areas where PA and GA are required onboard the ship.


## FEATURES

- Standalone PA and GA system made for the marine environment
- 19" rack w/screw terminals for ship cable network
- Power Amplifiers, 100 V line with alternative power output of 120W, 240W or 400W
- Provides monitoring of power amplifiers
- 6 zones selection + ALL
- Can be integrated PA/GA solution in combination with VINGTOR- STENTOFON ACM system
- Input for 3 microphone panels
- AUX / Alarm input
- Input from Talk-Back system
- Input from PABX (preselected zones)
- Mains 110 - 230 V AC/24 V DC w/auto switch-over
- Built-in pre-amplifiers
- Wide set of microphones and alarm panels

## APPROVALS

The SPA system is tested according to EN60945, and is type approved by DNV, RMRS, CCS, RRR, CRS, GL, Lloyds, ABS, and BV





# SPA MAIN UNITS



- Steel cabinet, black
- Input for 3 microphone panels
- Input from Talk-back system
- PABX Input with zone presets.
- 6 zones relay output 100 V for speakers
- Prepared for 2 alarm panels and alarm module
- Alarm mute relay during PA message
- Powered by 230 VAC main and 24V DC Emergency, 230V AC main / 230V AC from UPS
- 115 VAC on request
- 2A Power included 230 VAC / 24 VDC
- Dimensions: 19" 12HU-24HU
- Protection class IP-22

2340130000

## SPA STANDARD 12HU PACKAGE 1

- Free space for 1 x VPA-xxx-V2 Poweramplifier
- SPA-EE3-V2
- SPA-AL-REL-V2
- SPA-CHIME-V2
- SPA-UPS incl power failure
- Power 2 x 230VAC & 24VDC
- Mounting plate for other options



Size (WxHxD): 525 x 600 x 525 mm Weight: 28.0 kg

Additional Information: For 24VDC failure output 3005010176 SPA-REL-V2 must be used

2340130001

## SPA STANDARD 16HU PACKAGE 2

- Free space for 2 x VPA-xxx-V2 Poweramplifier
- SPA-EXPW
- SPA-EE3D-V2
- SPA-AL-REL-V2
- SPA-CHIME-V2
- SPA-MUL-V2
- SPA-UPS incl power failure
- Power 2 x 230VAC & 24VDC
- Mounting plate for other options



Size (WxHxD): 525 x 765 x 525 mm Weight: 35.0 kg

Additional Information: For 24VDC failure output 3005010176 SPA-REL-V2 must be used

3005010079

## SPA-120-V2 "PA MAIN UNIT,19" RACK 1X120W VPA AMPLIFIER



Size (WxHxD): 525 x 600 x 525 mm Weight: 42.0 kg

Additional Information: Base model 12HU Feature cards to be specified, see internal accessories

3005010188

## SPA-TERM-V2 TERMINAL BOARD SPA W/2.5M CABLE

- Optional Assembly-set consisting of main board on plate with cables.
- Plate with space for other modules
- Includes 2A power supply 230 VAC / 24 VDC



Size (WxH): 485 x 600 mm Weight: 3.0 kg

Additional Information: Base model 12HU Feature cards to be specified, see internal accessories

3005010084

## SPA-240-V2 "PA MAIN UNIT,19" RACK 1X240W VPA AMPLIFIER

Size (WxHxD): 525 x 600 x 525 mm Weight: 45.0 kg

Additional Information: Base model 12HU Feature cards to be specified, see internal accessories

3005010134

## SPA-EXP RACK EXPANSION WITHOUT WIRING IN STEP OF 4HU

3005010087

## SPA-400-V2 "PA MAIN UNIT,19" RACK 1X400W VPA AMPLIFIER


Size (WxHxD): 525 x 600 x 525 mm Weight: 48.0 kg

Additional Information: Base model 12HU Feature cards to be specified, see internal accessories

3005010135

## SPA-EXPW RACK EXPANSION WITH WIRING FOR ADDITIONAL AMPLIFIERS - 1 PER AMP 4HU

# SPA ACCESSORIES



3005010180

## SPA-SHELF SHELF FOR ADDITIONAL EQUIPMENT

- 19" System



**Size (WxHxD):** 492 x 133 x 390 mm  
**Weight:** 2.3 kg

Additional Information: Assembly included

3005010181

## SPA-SHELF4 SHELF W/DRAWER F/CU-SYSTEM INCL. RACK EXPANSION 3HU

- 19" System



**Size (WxHxD):** 492 x 133 x 390  
**Weight:** 7.2 kg

Additional Information: Assembly included

3005010235

## VPA-120 POWER AMPLIFIER, 120W

- Power amplifier in a 19" rack cabinet
- 100 V and 8 ohm output
- Dual inputs with priority switching
- Temperature controlled, forced back-to-front ventilation
- 115/230 VAC mains and 24 VDC battery backup
- Power consumption at 0dB 24V DC 7,5 A
- Power consumption at 0dB 230V AC 1.7 A
- Pilot tone line monitoring
- 24 VDC / 800 mA power output for external equipment
- Chime signal with on/off switch



**Size (WxHxD):** 482 x 133 x 420 mm "3HU"  
**Weight:** 18.2 kg

Additional Information: Requires 4HU in rack  
Tested according to EN 60945, IACS E10, IEC 60533

3005010237

## VPA-240 POWER AMPLIFIER, 240W

- Power amplifier in a 19" rack cabinet
- 100 V and 8 ohm output
- Dual inputs with priority switching
- Temperature controlled, forced back-to-front ventilation
- 115/230 VAC mains and 24 VDC battery backup
- Power consumption at 0dB 24V DC 15,4 A
- Power consumption at 0dB 230V AC 3.1 A
- Pilot tone line monitoring
- 24 VDC / 800 mA power output for external equipment
- Chime signal with on/off switch



**Size (WxHxD):** 482 x 133 x 420 mm "3HU"  
**Weight:** 21.2 kg

Additional Information: Requires 4HU in rack  
Tested according to EN 60945, IACS E10, IEC 60533

3005010239

## VPA-400 POWER AMPLIFIER, 400W

- Power amplifier in a 19" rack cabinet
- 100 V and 8 ohm output
- Dual inputs with priority switching
- Temperature controlled, forced back-to-front ventilation
- 115/230 VAC mains and 24 VDC battery backup
- Power consumption at 0dB 24V DC 28,0 A
- Power consumption at 0dB 230V AC 5.4 A
- Pilot tone line monitoring
- 24 VDC / 800 mA power output for external equipment
- Chime signal with on/off switch



**Size (WxHxD):** 482 x 133 x 420 mm "3HU"  
**Weight:** 24.2 kg

Additional Information: Requires 4HU in rack  
Tested according to EN 60945, IACS E10, IEC 60533

3005010184

## SPA-SWITCH-V2 MONITOR W/6X VOLUME LINE SELECTOR AND 6X PROGRAM SWITCH 2HU

- 6 Line input selector
- Monitoring for six amplifiers
- Entertainment input for six sources
- On/Off for entertainment
- Volume adjustment of line output signal with amplifier
- 24VDC supply
- All input/output terminals in back side
- 19" rack mounted 2 HU



**Size (WxH):** 483 x 89 mm  
**Weight:** 0.65 kg

Additional Information: Optional entertainment sources,  
assembly included

3005010185

### SPA-SWITCH-V3 6X PROG & LINE - SELECTOR SWITCH VOLUME CONTROL IN FRONT

- 6 Line input selector
- Monitoring for six amplifiers
- Entertainment input for six sources .
- On/Off for entertainment
- Volume adjustment of line output signal with amplifier
- 24VDC supply
- All input/output terminals in back side
- 19" rack mounted 2 HU
- Entertainment input 2 and 3 have each built-in preamplifier with volume adjustment for the input signal



Size (WxH): 483 x 89 mm Weight: 0.65 kg

Additional Information: Optional entertainment source, assembly included

3005010173

### SPA-RCD RADIO/CD PLAYER INCLUDING RACK EXPANSION 2U

- FM with RDS / MW / CD / MP3
- Mono-mixed 0dB output
- Delivered with power supply 230V AC /12V DC

Size (WxH): 483 x 89 mm

Additional Information: Optional entertainment source, assembly included

3005010169

### SPA-PABXR-V2 PABX RECALL VOICE REC MOD 1HU-RACK EXP INCL

- Recall voice recorder for PABX interface
- Using DTMF tone from PABX
- Up to 6 different zones or All can be given



Size: 19" wide, 1HU high

Additional Information: Assembly included

3005010111

### SPA-DARP-16 DIGITAL AUDIO RECORDER/PLAYER IN 19" 1U, 24V DC, FOR 7 MESSAGES, 960 SEC TOT.

- 7 different messages
- Maximum memory capacity 960 seconds.
- Front panel with key access to operate the device manually
- LEDs for status indication and message selection
- Protected stop-button to cancel ongoing messages
- Microphone and aux line inputs for recording
- Rear panel with connectors for remote control/ switches.
- Potential-free switching for message indication.



Size: 19" wide, 1HU high Weight: 2.8 kg

Additional Information: 2340110008 SPA-DARP-MIC Recording microphone Dynamic XLR-3pin. Remote panel for SPA-DARP-16 is SPA-REM7. Assembly included

2329990003

### DVD-191U DVD PLAYER RACKMOUNT 19" - 1HU

- Extensive Bi-Directional RS-232 Control
- Power on play
- Screen saver Function
- Format Adjustment for 4:3 and 16:9
- Slow motion and Frame by Frame playback
- Optical Digital Audio Outputs
- Plays DVD Video, DVD Audio (2 channel only) VCD, SVCD;DVD+R/+RW, and Audio CD
- Plays MP3, WMA, WAV, JPEG, ASF, MPEG2/MPEG1, DivX
- Defeatable On-Screen Guide Icons
- Composite, Component, and S-Video Outputs
- HDMI (High Definition Multimedia Interface)
- IR Remote Control Included
- Selectable Scan Mode
- DVD Audio Bonus Group Playback (Bonus group password required. Refer to disc for password.)
- Tray Lock (prohibits unwanted disc ejection)
- True Progressive Scan
- FVPP (Fine Video Picture Processing)
- Plays NTSC and PAL discs (region codes apply)




Size (WxHxD): 482 x 44 x 269 mm "1HU"  
Weight: 2,3 kg

Additional Information:  
Power 120 VAC, 60 Hz / 230 VAC, 50 Hz




# SPA INTERNAL ACCESSORIES



3005010166

## SPA-MUL-V2 SPA- ZONE CONTROL BOARD WITH 4 WIRE ENTERTAINMENT 6 ZONES

- Board for zone distribution when more than one amplifier is used
- Internal or external 24V override
- Configuration settings by jumpers.
- Interconnections to main terminal board by RJ45 8pin plug
- Pluggable screw terminals for external connections.



Additional Information: Optional rack unit

3005010109

## SPA-CHIME-V2 CHIME GENERATOR

- Will give a dual tone "Ding-dong" before PA message
- Interconnections to main terminal board by RJ45 8pin plug
- Pluggable screw terminals for external connections



Additional Information: Optional rack unit

2990000032

## CPM-SNT-120-5 POWER SUPPLY 100-240VAC/24VDC 5A

- Switch mode, regulated power
- 22.5 to 29.5 V DC (adjustable via potentiometer on front)
- Overload protected
- Short-circuit protected
- DIN rail mounting
- GL approved




Size (WxHxD): 40 x 130 x 125 mm Weight: 0.7 kg

Additional Information: 2990000033 CPM-SNT-250-10 Powersupply 230 VAC/24 VDC, 10A 2990000035 CPM-SNT-500-20 POWERSUPPLY 230 VAC/24 VDC, 20A

3005010121

## SPA-EE3D-V2 ALARM SET FOR DUAL SYSTEM

- Consist of 2x SPA-EE3 and 1x SPA-EE3 DUAL-AL
- A selector can set all required configuration of alarm tones.
- The module has three start inputs and three outputs for relay or lamps
- Interconnections to main terminal board by RJ45 8-pin plug




Size: 19" 1HU

Additional Information: Mounted on 1HU ventilation panel, Assembly and customized programming included

3005010124

## SPA-EE3-V2 SINGLE ALARM GEN. W/3 ALARM TONES

- The module has a microprocessor that administers the alarm tones and sets up the inputs and outputs
- A selector can set all required configuration of alarm tones
- The module has three start inputs and three outputs for relay or lamps
- Interconnections to main terminal board by RJ45 8pin plug




Size: 19" 1HU Weight: 0.5 kg

Additional Information: Mounted on 1HU ventilation panel, Assembly included. 1190900101 SPA-EE3-V2/PROG Custom alarm tone programming for EE3-V2

3005010102

## SPA-AL-REL-V2 3 X POT. FREE RELAY OUTPUT AS FOLLOWS

- GA-steady
- GA-pulsing
- GA-pulsing with mute
- Contact set rated at 230 VAC or 24 VDC



Additional Information: Optional rack unit  
SPA-AL-REL6-V2 O.no. 3005010101

3005010127

## SPA-EMS-V2 SWITCHING BOARD FOR EMERGENCY PA MESSAGE

- Used to combine All and Talk button to make emergency PA calls with single push



Additional Information: Optional rack unit

3005010176

### SPA-REL-V2 MULTIPURPOSE POTENTIAL FREE RELAY CONTACT FUNCTION TO BE SPECIFIED

- Contact set rated at 230 VAC or 24 VDC
- Rail mounting NS-35
- 2x contact set
- 24 VDC input coil




Additional Information: Optional rack unit

3005010130

### SPA-ENT4-V2 SPA 4 WIRE ENTERTAINMENT 6 ZONES

- Board for configuration to entertainment zones with 24V override
- Internal or external 24V override
- Configuration settings by jumpers
- Interconnections to main terminal board by RJ45 8pin plug
- Pluggable screw terminals for external connections




Additional Information: Optional rack unit

1152101000

### EXTRA TERMINAL WITH WIRING - WEIDMUELLER

- One unit needed for each termination point



Additional Information: Cable and assembly included

3005010132

### SPA-ENTP2-V2 2X INDEPENDENT ENTER SYSTEM W/2 X PROG, ZONE SELECTION, OVERRIDE

- For connection of 2 entertainment amplifiers
- 2 entertainment input
- On-Off for entertainment
- PA-zone selection by jumpers 1-6
- Priority output
- PA-input
- 2 PA-outputs

Additional Information: Optional rack unit

3005010068

### CAT-5 CABLE SPLITTER FOR RJ45

- Expander for interconnection of 2 additional boards to a Terminal board
- See expander list:
- 2 x SPA-MUL3-V2 or 2 x SPA-MUL4-V or 2 x SPA-EMS-V or
- 2 x SPA-AL-REL-V2 or. 2 x SPA-VDR-V2



Size (WxH): 40 x 80 mm Weight: 0.05 kg

Additional Information: Optional rack unit

3005010045

### MI-2 PREAMPLIFIER MIC. 24V DC W/RELAY, REV. 1

- For microphone
- 24V DC
- Rail mounting NS-35



Size (WxH): 45 x 70 mm

Additional Information:  
O.no. 3005010047 Preamplifier AUX/ENT. 24V DC

3005000038

### SMIII-PA PA TELEPHONE INTERFACE (TRUNK LINE NEEDED PER PA-LINE)

- Trunk input / Audio output
- 24V DC Input
- Rail mounting NS-35



Size (WxH): 45 x 70 mm

Additional Information: For connection to telephone exchanges

3005010136

### SPA-FAIL POWER FAILURE OUTPUT RELAY WITH POTENTIAL FREE CONTACT

- Contact set rated at 230V AC or 24V DC 6A
- Rail mounting NS-35
- 230V AC & 24V DC input




Size (WxH): 45 x 70 mm Weight: 0.1kg

Additional Information:  
O.no. 2340120001 115VAC/24DC  
O.no. 2340120002 115VAC/115VAC

3005010189

### SPA-UPS AUTO SWITCH BETWEEN 230AC MAIN & EMERG./UPS INCL. POWER FAILURE

- 230V AC 2A , 50/60Hz
- Rail mounting NS-35



Additional Information: Optional rack unit  
O.no. 2890010002 115VAC

3005010191

### SPA-VDR-V2 OUTPUT FOR VOICE DATA RECORDER

- 0dB and switch for all PA-or alarm activities
- Interconnections to main terminal board by RJ45 8pin plug
- Pluggable screw terminals for external connections



Additional Information: Optional rack unit

2340120009

### SPA-REL-V3 MULTIPURPOSE POTENTIAL FREE RELAY CONTACT WITH FUSED OUTPUTS

- Contact set 230V AC, 2A
- Rail mounting NS-35
- 2x contact set
- 24 VDC input coil




Additional Information: Optional rack unit

2340120010

### SPA-REL-V4 MULTIPURPOSE POT. FREE RELAY W/ FUSED OUTPUTS, 230VAC

- Contact set rated at 115 - 230 VAC or 24 VDC
- Rail mounting NS-35
- 2x contact set
- 24V DC input coil



Additional Information: Optional rack unit

# SPA ANNOUNCEMENT & ALARM PANELS



3005010146

## SPA-M1H-V2 PA PANEL SINGLE FOR ALL CALL - FLUSH - W/ HANDHELD MIC ETC-1-TB

- PA Panel for single system, all call
- Delivered with handheld microphone
- Built-in pre-amplifier with preset signal level and tone controls
- TALK button on panel and handheld microphone
- Flush mounting, back box for wall mounting is available
- Local mute contact for external loudspeaker



Size (WxHxD): 144 x 144 x 82 mm Weight: 0.5 kg

Additional Information: IP-44

3005010149

## SPA-M1S-V2 PA PANEL SINGLE FOR ALL CALL - FLUSH - W/ GOOSENECK MIC MB-30G

- PA Panel for single system, all call
- Delivered with gooseneck microphone
- Built-in pre-amplifier with preset signal level and tone controls
- TALK button on panel for All Call message
- Flush mounting, back box for wall mounting is available
- Local mute contact for external loudspeaker



Size (WxHxD): 144 x 144 x 82 mm Weight: 0.5 kg

Additional Information: IP-44

3005010145

## SPA-M1H-D PA PANEL DUAL FOR ALL CALL - FLUSH - W/ HANDHELD MIC ETC-1-TB

- PA Panel for dual system , all call
- Delivered with handheld microphone
- Built-in pre-amplifier with preset signal level and tone controls
- TALK button on panel and handheld microphone
- Flush mounting, back box for wall mounting is available
- Local mute contact for external loudspeaker



Size (WxHxD): 144 x 144 x 82 mm Weight: 0.5 kg

Additional Information: IP-44

3005010148

## SPA-M1S-D PA PANEL DUAL FOR ALL CALL - FLUSH - W/ GOOSENECK MIC MB-30G

- PA Panel for dual system , all call
- Delivered with handheld microphone
- Built-in pre-amplifier with preset signal level and tone controls
- TALK button for All call message
- Flush mounting, back box for wall mounting is available
- Local mute contact for external loudspeaker



Size (WxHxD): 144 x 144 x 82 mm Weight: 0.5 kg

Additional Information: IP-44

3005010158

## SPA-M6H-V2 PA PANEL SINGLE W/6 ZONES, ALL CALL AND DIMMER - FLUSH - W/HANDHELD MIC ETC-1-TB

- PA-panel for single system
- Built-in pre-amplifier with preset signal level and tone controls
- 6 zone selection buttons
- ALL, TALK and dimmer buttons.
- Replaceable text label for each zone button
- Zone buttons have activation confirmation light
- Flush mounting, back box for wall mounting is available
- Local mute contact for external loudspeaker



Size (WxHxD): 144 x 144 x 82 mm Weight: 0.5 kg

Additional Information: IP-44

O.no. 2340110001 SPA-M6HM-V2 version with zone memory

3005010161

### SPA-M6S-V2 PA PANEL SINGLE W/6 ZONES, ALL CALL AND DIMMER FLUSH W/GOOSENECK MIC MB-30G

- PA-panel for single system
- Built-in pre-amplifier with preset signal level and tone controls
- 6 zone selection buttons
- ALL, TALK and dimmer buttons.
- Replaceable text label for each zone button
- Zone buttons have activation confirmation light
- Flush mounting, back box for wall mounting is available
- Local mute contact for external loudspeaker



Size (WxHxD): 144 x 144 x 82 mm Weight: 0.5 kg

Additional Information: IP-44  
O.no. 2340110002 SPA-M6SM-V2 version with zone memory

3005010095

### SPA-AC6 SINGLE ALARM PANEL WITH COVERED AND ILL. ALARM START AND RESET BUTTON FOR INDOOR USE

- Alarm panel for single system
- Activating abandon, general or manual alarms
- Alarm reset button
- Replaceable text label for each button
- Separate Emergency button (EMS) for PA-message.
- Hinged transparent protecting cover all buttons
- To be used together with SPA-M6
- Flush mounting, back box for wall mounting is available



Size (WxHxD): 96 x 144 x 82 mm Weight: 0.4 kg

Additional Information: IP-44

3005010157

### SPA-M6H-D PA PANEL DUAL W/6 ZONES, ALL CALL AND DIMMER FLUSH W/HANDHELD MIC ETC-1-TB

- PA-panel for dual system
- Delivered with handheld microphone
- Built-in pre-amplifier with preset signal level and tone controls
- 6 zone selection buttons
- ALL, TALK and dimmer buttons.
- Replaceable text label for each zone button
- Zone buttons have activation confirmation light
- Flush mounting, back box for wall mounting is available
- Local mute contact for external loudspeaker



Size (WxHxD): 144 x 144 x 82 mm Weight: 0.5 kg

Additional Information: IP-44  
O.no.2340110003 SPA-M6HDM-V2 version with zone memory

3005010096

### SPA-AC6-D DUAL ALARM PANEL W. COVERED AND ILL. ALARM START AND RESET BUTTON FOR INDOOR USE

- Alarm panel for dual system
- Activating abandon, general or manual alarms
- Alarm reset button
- Replaceable text label for each button
- Separate Emergency button (EMS) for PA-message.
- Hinged transparent protecting cover all buttons
- To be used together with SPA-M6D
- Flush mounting, back box for wall mounting is available



Size (WxHxD): 96 x 144 x 82 mm Weight: 0.4 kg

Additional Information: IP-44

3005010160

### SPA-M6S-D PA PANEL DUAL W/6 ZONES, ALL CALL AND DIMMER FLUSH W/GOOSENECK MIC MB-30G

- PA-panel for dual system
- Delivered with gooseneck microphone
- Built-in pre-amplifier with preset signal level and tone controls
- 6 zone selection buttons
- ALL, TALK and dimmer buttons.
- Replaceable text label for each zone button
- Zone buttons have activation confirmation light
- Flush mounting, back box for wall mounting is available
- Local mute contact for external loudspeaker



Size (WxHxD):144 x 144 x 82 mm mm Weight: 0.6 kg

Additional Information: IP-44  
O.no. 2340110004 SPA-M6SDM-V2 version with zone memory

2340300002

### SPA-AC1P GENERAL ALARM BUTTON WITH COVER, FLUSH / WALL MOUNT-PULS

- Activating general alarms
- Flush mounting, back box for wall mounting is available



Size (WxHxD): 96 x 96 x 82 mm Weight: 0.25 kg

Additional Information: 3005010105 SPA-BOXM1 wall mounting box

2340300001

### SPA-AC1PW GEN. ALARM BUTTON W/COVER,FLUSH/WALL MOUNT WATERTIGHT-PULS

- Activating general alarms



Size (WxHxD): 110 x 80 x 63 mm Weight: 0.53kg

Additional Information: IP-66

3005010199

### SPA-W1-V2 WEATHERPROOF PA-PANEL FOR OUTDOOR USE

- Weatherproof PA panel for single system
- Built-in pre-amplifier with preset signal level and tone controls
- Microphone with PTT
- Contact for WP handheld microphone P-66 or P-66/10
- Wall mounting outdoors/indoors
- Local mute contact for external loudspeaker



Size (WxHxD): 140 x 230 x 125 mm Weight: 0.5 kg

Additional Information: IP-66

3005010197

### SPA-W1-D WEATHERPROOF PA-PANEL FOR OUTDOOR USE

- Weatherproof PA panel for dual system
- Built-in pre-amplifier with preset signal level and tone controls
- Connector for WP handheld microphone P-66 or P-66/10
- Wall mounting outdoors/indoors
- Local mute contact for external loudspeaker



Size (WxHxD): 140 x 230 x 125 mm Weight: 0.5 kg

Additional Information: IP-66

3005010196

### SPA-W1AR-V2 WEATHERPROOF PA AND ALARM PANEL FOR OUTDOOR USE

- Weatherproof PA and Alarm Panel for single system
- General or manual alarms
- Built-in pre-amplifier with preset signal level and tone controls.
- Buttons with hinged transparent protecting cover
- Connector for WP handheld microphone P-66 or P-66/10
- Replaceable text label for each button
- Wall mounting outdoors/indoors
- Local mute contact for external loudspeaker



Size (WxHxD): 140 x 230 x 125 mm Weight: 0.5 kg

Additional Information: IP-66

3005010195

### SPA-W1AR-D DUAL WEATHERPROOF PA AND ALARM PANEL FOR OUTDOOR USE

- Weatherproof PA and Alarm Panel for single system
- General or manual alarms
- Built-in pre-amplifier with preset signal level and tone controls.
- Buttons with hinged transparent protecting cover
- Connector for WP handheld microphone P-66 or P-66/10
- Replaceable text label for each button
- Wall mounting outdoors/indoors
- Local mute contact for external loudspeaker



Size (WxHxD): 140 x 230 x 125 mm Weight: 0.5 kg

Additional Information: IP-66

3005010202

### SPA-W6A4 WEATHERPROOF PA AND ALARM PANEL W/6 ZONES FOR OUTDOOR USE

- Weatherproof PA and Alarm panel for single system
- Abandon, general or manual alarms
- Contact for WP handheld microphone P-66 or P-66/10
- Built-in pre-amplifier with preset signal level and tone controls.
- 6 zone selection buttons
- Alarm buttons with hinged transparent protecting cover for protection against unauthorized use
- Microphone with PTT
- Connector for WP handheld microphone P-66 or P-66/10
- Replaceable text label for each button.
- Wall mounting, outdoor or indoor
- Local mute contact for external loudspeaker



Size (WxHxD): 140 x 230 x 125 mm Weight: 0.7 kg

Additional Information: IP-66

3005010203

### SPA-W6A4-D DUAL WEATHERPROOF PA- ND ALARM PANEL W/6 ZONES FOR OUTDOOR USE

- Weatherproof PA and Alarm panel for single system
- Abandon, general and manual alarms
- Contact for WP handheld microphone P-66 or P-66/10
- Built-in pre-amplifier with preset signal level and tone controls.
- 6 zone selection buttons
- Alarm buttons with hinged transparent protecting cover for protection against unauthorized use
- Microphone with PTT
- Connector for WP handheld microphone P-66 or P-66/10
- Replaceable text label for each button.
- Wall mounting, outdoor or indoor
- Local mute contact for external loudspeaker



Size (WxHxD): 140 x 230 x 125 mm Weight: 0.7 kg

Additional Information: IP-66

3005020039

### P-66 HAND MICROPHONE WITH PLUG, WT

- Weatherproof, salt water resistant handheld microphone
- Suitable for heavy-duty outdoor operation subject to noise disturbance
- Delivered with 2 meter flexible cable and plug
- For use in Public Address System and Talk-Back



Size (WxHxD): 54 x 82 x 55mm Weight: 0.3 kg

Additional Information: IP-54

3005020040

### P-66/10 HAND MICROPHONE WITH PLUG AND 10 M CABLE, WT

- Weatherproof, salt water resistant handheld microphone
- Suitable for heavy-duty outdoor operation subject to noise disturbance
- Delivered with 10 meter cable and plug
- For use in Public Address System and Talk-Back



Size (WxHxD): 54 x 82 x 55mm Weight: 0.3 kg

Additional Information: IP-54

3005020029

### ETC-1-TB HANDMIC W/5 PIN DIN PLUG

- Dynamic, 200 ohm
- Flexible cord with PTT switch
- Hang up clip
- For ETB and CTB central panels



Size (WxHxD): 58 x 102 x 47mm Weight: 0.2 kg

Additional Information: IP-22

3005020028

### ETC-1-CH CHASSIS CONTACT 5-PIN DIN FOR ETC-1-TB W/1M CABLE

- Prepared with screw terminals for connections



Size PCB (WxHxD) : 50 x 35 x 16mm Weight: 0.1 kg

3005010177

### SPA-REM7 REMOTE PANEL W/ 7 START & 1 STOP BUTTON

- Message play panel
- Seven start buttons for play message
- One message stop button
- For DARP-16



Size (WxHxD): 144 x 144 x 57 mm Weight: 0.4 kg

Additional Information: IP-22, Unit for SPA-DARP-16

3005010204

### SPA-WIRELESS/D DUAL ACT-52 WIRELESS RECEIVER WITH 2 X ACT-5H WIRELESS HAND MIC

- 2x Antennas
- External 100-240V AC Switching Power Supply
- Rack mounting kit ,optional



Size receiver (WxHxD): 210 x 44 x 206 mm Weight: 0.9 kg Microphone 0,2 kg

3005010172

### SPA-PROG4-RDF ENTERTAINMENT PROGR SELECTOR DUAL FAILSAFE, 4 PROG. INPUTS PA A&B WITH OVERRIDE

- Selector for 4 100V entertainment programs
- PA input 100V from dual A-B system
- PA override 24VDC input failsafe from dual A-B system and for single system by DIP switch
- 2 common outputs 100V for dual A-B system



Size (WxHxD): 144 x 144 x 82 mm Weight: 0.4 kg

Additional Information: IP-22

3005010024

### ENT-4F BEDSIDE TYPE PANEL W/ VOL. CONTROL AND PROGRAM SELECTOR, FAILSAFE

- Entertainment panel
- Input for 4 program sources 100v
- Program selector and volume control
- Input for emergency line 100v
- Input for 24VDC failsafe override
- Optional entertainment sources



Size (WxHxD): 252 x 100 x 59 mm Weight: 0.475 kg

Additional Information: IP-22

3005010205

### SPA-WIRELESS-MIC ACT-51 1CH RECEIVER W/ACT-5H HANDMIC

- 2x Antennas
- Power supply External AC Adapter, 12-15V DC, 1A
- Rack mounting kit, optional



Size receiver (WxHxD): 210 x 44 x 206 mm Weight: 0.7 kg Microphone 0,2 kg

3005010103

### SPA-ANT/ D DUAL EXTERNAL ANTENNA SET FOR SPA-WIRELESS/D

- Antenna set for SPA-WIREL
- With cable and plug



Size (HxØ): 165 x 150mm Weight: 0.142kg

Additional Information:

3005010210

### VM15-R VOLUME CONTROL - 4 WIRE OVERRIDE, FLUSH 15W

- Volume control, 4 wire override 15W
- For use in SPA-V2 Public address and general alarm system
- For flush mounting
- Optional, wall mounting with back box



Size (WxHxD): 96 x 96 x 80 mm Weight: 0.4 kg

Additional Information: Backbox SPA-BOXM1

3005010213

### VM50-R VOLUME CONTROL - 4 WIRE OVERRIDE, FLUSH 50W

- Volume control, 4 wire override 15W
- For use in SPA-V2 Public address and general alarm system
- For flush mounting
- Optional, wall mounting with back box



Size (WxHxD): 96 x 96 x 80 mm Weight: 0.4 kg

Additional Information: Backbox SPA-BOXM1

3005010215

### VM50-RDF VOLUME CONTR. 2X50W DUAL W/ OVERRIDE RELAY FAIL SAFE - FLUSH

- Dual volume control, 4 wire override 2x 50W
- For use in SPA-V2 Public address and general alarm system
- For flush mounting
- Optional, wall mounting by using back box



Size (WxHxD): 144 x 144 x 82 mm Weight: 0.7 kg

Additional Information: Backbox STBOKS5

3005010212

### VM15-RDF VOLUME CONTR. 2X15W DUAL W/ OVERRIDE RELAY FAIL SAFE - FLUSH

- Dual volume control, 4 wire override 2x 15W
- For use in SPA-V2 Public address and general alarm system
- For flush mounting
- Optional, wall mounting by using back box



Size (WxHxD): 144 x 144 x 82 mm Weight: 0.7 kg

Additional Information: Backbox STBOKS5

3005010211

### VM15-RD DUAL VOLUME CONTROL - 4 WIRE OVERRIDE, FLUSH 2X15W

- Dual volume control, 4 wire override 2x 15W
- For use in SPA-V2 Public address and general alarm system
- For flush mounting
- Optional, wall mounting by using back box



Size (WxHxD): 144 x 144 x 82 mm Weight: 0.7 kg

Additional Information: Backbox STBOKS5

3005010214

### VM50-RD DUAL VOLUME CONTROL - 4 WIRE OVERRIDE, FLUSH 2X50W

- Dual volume control, 4 wire override 2x 50W
- For use in SPA-V2 Public address and general alarm system
- For flush mounting
- Optional, wall mounting by using back box




Size (WxHxD): 144 x 144 x 82 mm Weight: 0.7 kg

Additional Information: Backbox STBOKS5

3005010206

### STBOKS5 WALL MOUNTING BOX FOR VM15 AND 50RD



Size (WxHxD): 144 x 144 x 59 mm Weight: 0.22 kg

3005010105

### SPA-BOXM1 WALL MOUNTING BOX FOR VM5, 15 AND 50R




Size (WxHxD): 96 x 96 x 78 mm

3005010155

### SPA-M6BOKS FOR SPA-M1 AND M6 PANELS WHEN WALL MOUNTED

- Wall mounting box for SPA-M1 & SPA-M6 PA-panels.
- For SPA public address and general alarm systems.
- Designed for indoor use



Size (WxHxD): 144 x 144 x 58 mm Weight: 0.3 kg

3005010003

### ACBOKS FOR SPA-AC6 PANELS WHEN WALL MOUNTED

- For SPA-AC6 & SPA-AC6-D alarm panels.
- Designed for indoor use.



Size (WxHxD): 96 x 144 x 58 mm Weight: 0.2 kg

Additional Information: Cable inlet 2x PG-16

## MANUALS & SPARES

A100K10369

SPA-V2 System Manual

A100K10370

SPA-V2 Configuration & Installation Manual

A100K10371

SPA-V2 User Guide

A100K10875

VPA-120/240/400 Configuration & Installation Manual

3005010182

SPAS-V2 Standard set of Spares

[www.zenitel.com](http://www.zenitel.com)

---

DOC NO

**A100K11298**

05.04.2016

[sales@zenitel.com](mailto:sales@zenitel.com)

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Vingtor-Stentofon products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice. ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend. Zenitel – All rights reserved.